

QuickLink[®]

Keyboard Wedge



The QuickLink, Compsee's keyboard wedge is state-of-the-art in user program flexibility, interchangeability between terminals and in its low-profile, lightweight design.

As a keyboard wedge, the QuickLink simply plugs in between the keyboard and terminal display.

As a gateway for external data input, the QuickLink can accept bar code data read from all popular input devices (Wand, Laser, CCD etc.), data read from a magnetic stripe reader, or RS 232 input from a portable data collection terminal, scale or slot scanner.

The input data to the QuickLink is decoded and transmitted to the display as if the data had been keyed in through the keyboard. The keyboard itself remains active at all times when the QuickLink is in-line.

If necessary, simple programming via menus or instructions downloaded from a PC allow the user to customize the unit to match the keyboard input required by their present software. The user can verify the input data to inhibit invalid data, as well as format the data to match screen input. The QuickLink is designed to eliminate as much as possible the manual entry of data.



COMPSEE[®]

INPUT OPTIONS

Bar Code Readers:

Contact.....	Wand, Badge Readers (Slot)
Non-Contact.....	Laser, CCD, Slot
Magnetic Stripe Readers....	Detached: Tracks 1, 2 or 1 & 2
RS 232 Auxiliary Port ..	Portable Terminals, Scales, Slot Scanners

INTERFACE OPTIONS - KEYBOARD INTERFACES

Adds	1010		
Apple	Macintosh	PowerBook	Quadra
AT&T	605	610	615
	705	715	4410
	4425	6386/SX	6500
	6528/29	UNIX	
Data General	211	214	215
	412	5220MTX	
DEC-Digital.....	220	240	320
	330	420	
Decision Data	3496	3497	3776
	3596	3597	3761
	3791	3781	
Dell	210 PC		
Epson	PC		
HP	700/60	700/41	700/43
	700/91	700/92	700/94
	Vectra	2392	2624
Honeywell	HDS-7		
IBM	PC	PC/XT	PC/AT
	PS/1	PS/2	Laptop 70
	3151	3161	3163
	3179	3180	3191
	3192	3196	3197
	3471	3472	3476
	3477	7546 PC	
Liberty.....	120		
Lynk.....	096	196/E	197 C/U
	Lite 1/2/3		
MAI Basic IV	1200	1400	1800
	DT-4313		
Memorex.....	2192	1196	1476
Orbit	155+		
Telex.....	191	197	78X-80X
	1192	1196	1197
	1476		
Toshiba.....	T 4400SX		
Unisys.....	B-26	T-27	
VisenTech	VS 220		
Wang	2110		
Wyse	30	50	75
	ALL - 105 Keyboards		
	ALL - ASCII Keyboards		
	ALL - PC Enhanced Keyboards		
	ALL - 108 Keyboards		

Inquire about other keyboard interfaces.

INTERFACE OPTIONS - POS - KEYBOARD INTERFACES

IBM	3653	3683	4683
NCR	280	2151	2152
	7052	2154	2155
Fujitsu	7770	7990	

RS 232 INTERFACE

Single Port RS 232

Dual Port (in-line) RS 232

BAR CODES SYMBOLOGIES

Auto-discriminates between the following symbologies:

Code 3 of 9	Industrial 2 of 5	UPC A
Code 3 of 9 Extended	Codabar	UPC E
Code 128	Code 11	EAN/JAN 8
Interleaved 2 of 5	Code 93	EAN/JAN 13
		Plessey

PROGRAM PARAMETERS

General Parameters	Terminal Type	Keyboard Type
	Enable Keyboard Functions	Laser Redundancy
	Preamble/Postamble (16 max)	Beeper Volume
	Mag Swipe Track Selection	Intercharacter Delay
	Buffer Enable/Disable	Interfunction Delay
	Input Inhibit Checking	Command Record Transmit
Bar Code Input Parameters	Code Enable/Disable	Code Length
	Check Digit Checks	Start/Stop Transmit
	Check Digit Transmit	Code ID Transmit
Serial Parameters	Preamble/Postamble (16 max)	Record Terminator
	Enable Keyboard Functions	Baud Rate
	Parity	Word Length
	Stop Bits	Protocol
	Dual Port Enable	Fixed Length Enable
	Transmit Path	
Input Data Edit Parameters.....	Qualify by Port	Add Data
	Qualify by Symbology	Delete Data
	Qualify by Length	Reformat Data
	Qualify by Data Match	Define 2 Output Formats
Keyboard Mapping Parameters	Single Key Positions	Data Records
	Multiple Key Positions	Function Records

ENVIRONMENTAL

Operating Temperature....	+5°C to +40° C
Storage Temperature	-20° C to +65° C
Relative Humidity.....	To 95% (Non-Condensing)

MECHANICAL

Length	7.3" (185mm)
Width.....	3.4" (86 mm)
Height	1.00" (25.4mm)
Weight	12 oz. (approx. weight with cable)

POWER REQUIREMENTS

No auxiliary power supply is required. Power is consumed from the terminal except when the QuickLink is interfaced to a Wyse 30, Wyse 60, NCR 7052 or for RS 232 output.



Post Office Box 1209 • Mt. Gilead, NC 27306

For sales information, call: Toll-free 800.628.3888

Phone 407.724.4321 • Fax 407.723.2895 • e-mail sales@compsee.com • www.compsee.com

QuickLink is a trademark of Compsee, Inc. Other products are trademarks or registered trademarks of their respective companies.

In a continuing effort to improve our products, Compsee, Inc. reserves the right to change specifications and features without prior notice